## NSN 5935-00-004-6610

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-004-6610

**Body Style:** 

Straight shape w/flange

**Overall Length:** 

Between 1.325 inches and 1.336 inches

**Overall Height:** 

Between 1.546 inches and 1.578 inches

Overall Width:

Between 1.546 inches and 1.578 inches

**Environmental Protection:** 

Pressure proof

**Unthreaded Mounting Hole Diameter:** 

Between 0.115 inches and 0.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 1.2475 inches and 1.2525 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.2475 inches and 1.2525 inches

**Distance From Mounting Shoulder To Front Face:** 

Between 0.688 inches and 0.698 inches

**Mating End Quantity:** 

2

**Contact Position Arrangement Style:** 

22-55 all mating ends

**Contact Removability:** 

Nonremovable all mating ends all contact groupings

**Contact Maximum Current Rating In Amps:** 

7.5 all mating ends all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:** 

500.0 all mating ends all contact groupings

**Contact Maximum Dc Voltage Rating In Volts:** 

700.0 all mating ends all contact groupings

**Polarization Method:** 

Keyway or multiple keyway

**Insert Position In Deg:** 

142.0

Shell Type:

Solid

**Connector Locking Method:** 

Bayonet pin

**Contact Material:** 

Copper alloy all mating ends all contact groupings

**Contact Surface Treatment:** 

Gold all mating ends all contact groupings and silver all mating ends all contact groupings

## **NSN 5935-00-004-6610** Connector Adapter - Page 2 of 2



Insert Material:
Rubber all mating ends
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Insert Material Specification:
Mil-r-3065 military specification single material response all mating ends
Included Contact Quantity:
55 2nd mating end all contact groupings
Included Contact Type:
Round socket 2nd mating end all contact groupings
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.110 gold grains, troy and 0.110 silver grains, troy
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-r-3065 spec.