## NSN 5935-00-005-2536

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-005-2536

**Body Style:** 

Straight edge type w/mounting flange

**Overall Length:** 

3.656 inches

**Overall Height:** 

0.641 inches

**Overall Width:** 

0.328 inches

**Unthreaded Mounting Hole Diameter:** 

0.125 inches

**Distance Between Mounting Facility Centers:** 

3.406 inches

**Board Accommodated Length:** 

2.953 inches single board

**Board Accommodated Width:** 

Between 0.054 inches and 0.071 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

Bridged contacts inserted board single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

7.5 single mating end single contact grouping

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping

**Terminal Type:** 

Tab, solder lug single mating end single contact grouping

**Insert Material Specification:** 

Mil-m-19833, type gdi-30 military specification single material response single mating end

**Included Contact Quantity:** 

18 single mating end single contact grouping

**Included Contact Type:** 

Bifurcated spring single mating end single contact grouping

## NSN 5935-00-005-2536

Electrical Receptacle Connector - Page 2 of 2



<b>Precious Material And Location:</b>
Contact surfaces gold
Precious Material And Weight:
0.018 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard): Mil-g-45204 spec.