Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-005-2723

### **Body Style:**

Straight edge type w/mounting flange

**Overall Length:** 

1.850 inches

# **Overall Height:**

0.660 inches

**Overall Width:** 

0.328 inches

#### **Unthreaded Mounting Hole Diameter:**

0.116 inches

### **Distance Between Mounting Facility Centers:**

1.531 inches

### **Board Accommodated Length:**

1.080 inches single board

### **Board Accommodated Width:**

Between 0.054 inches and 0.071 inches

### Mating End Quantity:

1

# Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

## Contact Removability:

Nonremovable single mating end single contact grouping

## Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

#### **Terminal Location:**

Back single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping

#### **Insert Material:**

Plastic diallyl phthalate single mating end

## **Contact Surface Treatment Specification:**

Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping

## **Terminal Type:**

Tab, solder lug single mating end single contact grouping

## Insert Material Specification:

Mil-m-19833, type gdi-30 military specification single material response single mating end

#### **Included Contact Quantity:**

12 single mating end single contact grouping

#### **Included Contact Type:**

Bifurcated spring single mating end single contact grouping



Precious Material And Location:

Contact surfaces gold

**Precious Material And Weight:** 

0.012 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.