NSN 5935-00-005-2745

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-005-2745

Body Style:

Straight shape, external coupling

Overall Length:

1.352 inches

Overall Height:

1.798 inches

Overall Width:

1.798 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof

Unthreaded Mounting Hole Diameter:

Between 0.115 inches and 0.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 1.431 inches and 1.441 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.431 inches and 1.441 inches

Distance From Mounting Shoulder To Front Face:

Between 0.516 inches and 0.546 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

37p single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

20.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Spring friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic single mating end

NSN 5935-00-005-2745

Electrical Receptacle Connector - Page 2 of 2



| Terminal Type: |
|--|
| Crimp single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Cadmium |
| Included Contact Quantity: |
| 37 single mating end single contact grouping |
| Included Contact Type: |
| Round socket single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.037 gold grains, troy |
| Precious Material: |
| Gold |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| |