

View Online at <https://aerobasegroup.com/nsn/5935-00-005-2776>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape, internal coupling w/strain relief

Body Length:

2.562 inches

Overall Diameter:

Between 1.658 inches and 1.666 inches

Environmental Protection:

Thermal shock resistant and vibration resistant and shock resistant and moisture resistant

Cable Entrance Diameter:

Between 1.147 inches and 1.177 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

61 number 20 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

0.0 and 24.0 and 135.0 and 199.0 and 240.0

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling ring

Connector Cable Strain Relief Method:

Cable clamp

Operating Temperature Rating:

Between -55.0 degrees celsius and 260.0 degrees celsius

Features Provided:

Pre-tinned terminal

Thready Qty Per Inch (tpi):

18

Thread Size:

1.562 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Rhodium and silver single mating end single contact grouping

Insert Material:

Rubber single mating end

Contact Surface Treatment Specification:

Qq-s-365 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Mil-c-26636 military specification single material response single mating end single contact grouping

Shell Material:

Stainless steel

Shell Surface Treatment:

Passivate

Shell Material Specification:

Qq-s-763 federal specification single material response

Insert Material Specification:

Zz-r-765 federal specification single material response single mating end

Included Contact Quantity:

61 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces rhodium and contact surfaces silver

Precious Material And Weight:

0.061 rhodium grains, troy and 0.061 silver grains, troy

Precious Material:

Rhodium and silver

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-c-26636 spec.