Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-005-8841

ть	read Class:
2a	
	read Direction:
	ght-hand
	bdy Style:
	aight shape, external coupling w/backshell  verall Length:
	352 inches
	rerall Height: tween 1.173 inches and 1.203 inches
	verall Width:
	tween 1.173 inches and 1.203 inches
	vironmental Protection:
	essure proof and moisture resistant and vibration proof
	nter To Center Distance Between Mounting Facilities Parallel To Height:
	tween 0.891 inches and 0.921 inches
	stance Between Centerlines Of Mounting Facilities Parallel To Body Width:
	tween 0.891 inches and 0.921 inches
	stance From Mounting Shoulder To Front Face:
	tween 0.516 inches and 0.546 inches
	readed Device Type:
	ck shell
	ating End Quantity:
1	
	ontact Position Arrangement Style:
-	single mating end
	ontact Removability:
	movable single mating end single contact grouping
	ontact Maximum Current Rating In Amps:
	.0 single mating end single contact grouping
	larization Method:
Ke	yway or multiple keyway
Ins	sert Position In Deg:
0.0	)
Sh	ell Type:
So	lid
Co	onnector Locking Method:
Sp	ring friction
Th	read Size:
1.0	000 inches
Те	rminal Location:
Ba	ck single mating end single contact grouping



#### **Contact Material:**

Copper alloy single mating end single contact grouping

#### Insert Material:

Plastic silicone single mating end

#### **Terminal Type:**

Crimp single mating end single contact grouping

#### Shell Material:

Aluminum alloy

## Included Contact Quantity:

7 single mating end single contact grouping

## Included Contact Type:

Round pin single mating end single contact grouping

# Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

#### Demilitarization:

No

Fiig:

A039b0