NSN 5935-00-005-8854

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-005-8854 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.490 inches **Overall Height:** Between 1.026 inches and 1.036 inches **Overall Width:** Between 1.026 inches and 1.036 inches **Environmental Protection:** Moisture resistant and salt water resistant and vibration proof Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.807 inches and 0.817 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.807 inches and 0.817 inches **Distance From Mounting Shoulder To Front Face:** Between 0.708 inches and 0.728 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 12-12 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin Thread Length: 0.290 inches Thready Qty Per Inch (tpi): 20

Thread Size:

0.750 inches

Fiig: A039b0

NSN 5935-00-005-8854 Electrical Receptacle Connector - Page 2 of 2



| Terminal Location: |
|--|
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Terminal Type: |
| Crimp single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Shell Material Specification: |
| Qq-a-367 federal specification single material response |
| Included Contact Quantity: |
| 12 single mating end single contact grouping |
| Included Contact Type: |
| Round socket single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.012 gold grains, troy |
| Precious Material: |
| Gold |
| Test Data Document: |
| 81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Thread Series Designator: |
| Unef |
| Specification Data: |
| 81349-mil-c-83723/71 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |