Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-005-8854

2a	a
Tł	hread Direction:
Ri	ight-hand
B	ody Style:
St	traight shape, external coupling
0	verall Length:
1.	490 inches
0	verall Height:
Be	etween 1.026 inches and 1.036 inches
0	verall Width:
Be	etween 1.026 inches and 1.036 inches
Eı	nvironmental Protection:
М	oisture resistant and salt water resistant and vibration proof
C	enter To Center Distance Between Mounting Facilities Parallel To Height:
Be	etween 0.807 inches and 0.817 inches
Di	istance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Be	etween 0.807 inches and 0.817 inches
Di	istance From Mounting Shoulder To Front Face:
Be	etween 0.708 inches and 0.728 inches
Tł	hreaded Device Type:
Ba	ack shell
М	ating End Quantity:
1	
C	ontact Position Arrangement Style:
12	2-12 single mating end
C	ontact Removability:
R	emovable single mating end single contact grouping
Pe	olarization Method:
Ke	eyway or multiple keyway
In	sert Position In Deg:
0.	0
SI	hell Type:
S	olid
C	onnector Locking Method:
Ba	ayonet pin
Tł	hread Length:
0.	290 inches
Tł	hready Qty Per Inch (tpi):
20	)
Tł	hread Size:
0.	750 inches



**Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping Shell Material: Aluminum alloy **Shell Material Specification:** Qq-a-367 federal specification single material response **Included Contact Quantity:** 12 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.012 gold grains, troy **Precious Material:** Gold **Test Data Document:** 81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Thread Series Designator:** Unef **Specification Data:** 81349-mil-c-83723/71 government specification Shelf Life: N/a Unit Of Measure:

**Demilitarization:** 

No

Fiig:

A039b0