

View Online at <https://aerobasegroup.com/nsn/5935-00-006-1279>

Body Style:

Straight shape, external coupling strain relief

Overall Height:

0.954 inches

Overall Width:

0.954 inches

Body Length:

1.776 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.145 inches and 0.155 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.719 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.719 inches

Cable Entrance Diameter:

0.178 inches

Distance From Mounting Shoulder To Front Face:

Between 0.452 inches and 0.462 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

10-6 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Connector Cable Strain Relief Method:

Cable clamp

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Rubber single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, class 1 military specification single treatment response all mating ends single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Included Contact Quantity:

6 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.030 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.