

View Online at <https://aerobasegroup.com/nsn/5935-00-006-5624>

Body Style:

Straight shape, internal coupling w/strain relief

Body Length:

2.081 inches

Overall Diameter:

1.531 inches

Environmental Protection:

Corrosion resistant and moisture resistant

Cable Entrance Diameter:

Between 0.615 inches and 0.635 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

20-39 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Potting

Connector Locking Method:

Bayonet latch

Connector Cable Strain Relief Method:

Cable clamp

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end all contact groupings

Terminal Type:

Solder well single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Included Contact Quantity:

37 single mating end 2nd contact grouping

Included Contact Type:

Round pin single mating end all contact groupings

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.047 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.