

View Online at <https://aerobasegroup.com/nsn/5935-00-007-1911>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape w/flange

Overall Length:

Between 2.110 inches and 2.140 inches

Overall Height:

Between 1.730 inches and 1.770 inches

Overall Width:

Between 1.730 inches and 1.770 inches

Unthreaded Mounting Hole Diameter:

Between 0.145 inches and 0.151 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 1.370 inches and 1.380 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.370 inches and 1.380 inches

Distance From Mounting Shoulder To Front Face:

Between 0.975 inches and 0.985 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

24-28 all mating ends

Contact Removability:

Removable all mating ends all contact groupings

Contact Maximum Current Rating In Amps:

22.0 all mating ends all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

200.0 all mating ends all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

250.0 all mating ends all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thread Length:

0.625 inches

Thready Qty Per Inch (tpi):

18

Thread Size:

1.500 inches

Contact Surface Treatment:

Gold all mating ends all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromium

Included Contact Quantity:

24 2nd mating end all contact groupings

Included Contact Type:

Round socket 1st mating end all contact groupings

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.048 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0