NSN 5935-00-007-4492

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-007-4492 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** Between 1.470 inches and 1.612 inches **Overall Height:** Between 1.605 inches and 1.645 inches **Overall Width:** Between 1.605 inches and 1.645 inches **Unthreaded Mounting Hole Diameter:** Between 0.175 inches and 0.181 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 1.245 inches and 1.255 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:** Between 1.245 inches and 1.255 inches **Distance From Mounting Shoulder To Front Face:** Between 0.750 inches and 0.766 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 22-2 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 73.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 900.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 1250.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

NSN 5935-00-007-4492

Electrical Receptacle Connector - Page 2 of 2



| Thread Size: |
|---|
| 1.375 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping and silver single mating end single contact grouping |
| Insert Material: |
| Rubber single mating end |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Cadmium |
| Included Contact Quantity: |
| 3 single mating end single contact grouping |
| Included Contact Type: |
| Round socket single mating end single contact grouping |
| Precious Material And Location: |
| Contact surface gold and contact surface silver |
| Precious Material And Weight: |
| 0.015 gold grains, troy and 0.015 silver grains, troy |
| Precious Material: |
| Gold and silver |
| Thread Series Designator: |
| Unef |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| |
| |