Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-007-5976

Body Style:
Right angle type
Overall Length:
3.700 inches
Overall Height:
0.564 inches
Overall Width:
0.386 inches
Unthreaded Mounting Hole Diameter:
0.093 inches
Distance Between Mounting Facility Centers:
3.400 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1000.0 single mating end single contact grouping
Polarization Method:
Contact to contact polarizing keys
Connector Locking Method:
Spring friction
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper single mating end single contact grouping
Contact Surface Treatment:
Gold and copper single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Pin single mating end single contact grouping
Insert Material Specification:
Mil-m-14, ty sdg military specification single material response single mating end
Included Contact Quantity:
59 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping



Precious Material And Location: Contact surfaces gold Precious Material And Weight: 0.059 gold grains, troy Precious Material: Gold Shelf Life: N/a Unit Of Measure: --

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.