NSN 5935-00-007-7303

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-007-7303

Body Style:

Straight edge type w/mounting flange

Overall Length:

5.405 inches

Overall Height:

0.406 inches

Overall Width:

0.438 inches

Unthreaded Mounting Hole Diameter:

0.125 inches

Distance Between Mounting Facility Centers:

5.093 inches

Board Accommodated Length:

4.640 inches single board

Board Accommodated Width:

Between 0.054 inches and 0.471 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Contact to contact polarizing keys

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Tab, solder lug single mating end single contact grouping

Contact Material Specification:

Qq-b-750 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-19833, type gdi-30 military specification single material response single mating end

Included Contact Quantity:

56 single mating end single contact grouping

NSN 5935-00-007-7303

Electrical Receptacle Connector - Page 2 of 2



Bifurcated spring single mating end single contact grouping
Precious Material And Location:
Contact surface gold
Precious Material And Weight:
0.056 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Included Contact Type:

Mil-std (military Standard):

Mil-m-19833 spec.

Fiig: A039b0