

View Online at <https://aerobasegroup.com/nsn/5935-00-007-7376>

Thread Class:

2a and 2b and 2a

Thread Direction:

Right-hand and right-hand and right-hand

Overall Length:

3.050 inches

Overall Height:

0.840 inches

Overall Width:

0.500 inches

Environmental Protection:

Salt water resistant and vibration resistant

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.295 inches and 0.305 inches

Distance Between Mounting Facility Centers:

Between 2.775 inches and 2.789 inches

Threaded Device Type:

Coupling facility and mounting stud

Mating End Quantity:

1

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Polarization Method:

Jackscrew

Connector Locking Method:

Jackscrew-socket

Thread Length:

0.350 inches

Thready Qty Per Inch (tpi):

40 and 40 and 40

Thread Size:

0.112 inches and 0.112 inches and 0.112 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Wire wrap single mating end single contact grouping

Contact Material Specification:

Qq-b-750, comp, b hard federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty sdg-f military specification single material response single mating end

Included Contact Quantity:

100 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.100 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc and unc and unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.