

View Online at <https://aerobasegroup.com/nsn/5935-00-007-8967>

Thread Class:

2a and 2a and 2b

Thread Direction:

Right-hand

Body Style:

T-shape

Overall Length:

0.984 inches

Overall Height:

0.734 inches

Environmental Protection:

Moisture resistant and vibration resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

3

Contact Position Arrangement Style:

Sm all mating ends

Contact Removability:

Nonremovable all mating ends single contact grouping

Contact Maximum Frequency Rating:

500.0 megahertz all mating ends all contact groupings

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell and internally threaded coupling ring

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends all contact groupings

Thread Size:

0.250 inches

Contact Material:

Copper alloy 3rd mating end all contact groupings

Contact Surface Treatment:

Gold all mating ends all contact groupings

Insert Material:

Plastic tetrafluoroethylene all mating ends

Contact Material Specification:

Qq-c-530, comp ht federal specification single material response 3rd mating end all contact groupings

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver

Shell Material Specification:

Qq-b-626, comp 22 federal specification single material response

Included Contact Quantity:

1 2nd mating end all contact groupings

Included Contact Type:

Coaxial socket 3rd mating end all contact groupings

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0