

View Online at <https://aerobasegroup.com/nsn/5935-00-008-0340>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

T-shape

Overall Length:

1.760 inches

Overall Height:

1.380 inches

Environmental Protection:

Moisture resistant and salt water resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.130 inches and 0.140 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

3

Contact Position Arrangement Style:

Nonstd all mating ends

Contact Removability:

Nonremovable all mating ends all contact groupings

Contact Maximum Current Rating In Amps:

10.0 all mating ends single contact grouping

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

32

Thread Size:

0.312 inches

Contact Material:

Copper alloy 360 all mating ends all contact groupings

Contact Surface Treatment:

Gold all mating ends all contact groupings and nickel all mating ends all contact groupings

Insert Material:

Glass all mating ends

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1 military specification 1st treatment response all mating ends all contact groupings and qq-n-290, cl 2 federal specification 2nd treatment response all mating ends all contact groupings

Contact Material Specification:

Mil-c-26656 military specification single material response all mating ends single contact grouping

Insert Material Specification:

Mil-m-24325 military specification single material response all mating ends

Included Contact Quantity:

1 2nd mating end all contact groupings

Included Contact Type:

Round socket all mating ends single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.003 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-26656 spec.