

View Online at <https://aerobasegroup.com/nsn/5935-00-008-0340>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

T-shape

**Overall Length:**

1.760 inches

**Overall Height:**

1.380 inches

**Environmental Protection:**

Moisture resistant and salt water resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

Between 0.130 inches and 0.140 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

3

**Contact Position Arrangement Style:**

Nonstd all mating ends

**Contact Removability:**

Nonremovable all mating ends all contact groupings

**Contact Maximum Current Rating In Amps:**

10.0 all mating ends single contact grouping

**Connector Locking Method:**

Externally threaded shell

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.312 inches

**Contact Material:**

Copper alloy 360 all mating ends all contact groupings

**Contact Surface Treatment:**

Gold all mating ends all contact groupings and nickel all mating ends all contact groupings

**Insert Material:**

Glass all mating ends

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 1 military specification 1st treatment response all mating ends all contact groupings and qq-n-290, cl 2 federal specification 2nd treatment response all mating ends all contact groupings

**Contact Material Specification:**

Mil-c-26656 military specification single material response all mating ends single contact grouping

**Insert Material Specification:**

Mil-m-24325 military specification single material response all mating ends

**Included Contact Quantity:**

1 2nd mating end all contact groupings

**Included Contact Type:**

Round socket all mating ends single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.003 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-c-26656 spec.