

View Online at https://aerobasegroup.com/nsn/5935-00-008-2464

Body Material: Plastic Thread Class: 2a Thread Direction: Right-hand Body Style: Top mount w/studs Overall Length:
Thread Class: 2a Thread Direction: Right-hand Body Style: Top mount w/studs
2a <b>Thread Direction:</b> Right-hand <b>Body Style:</b> Top mount w/studs
Thread Direction: Right-hand Body Style: Top mount w/studs
Right-hand Body Style: Top mount w/studs
Body Style: Top mount w/studs
Top mount w/studs
Overall Length:
-
1.344 inches
Overall Width:
0.438 inches
Mounting Hole Diameter:
0.125 inches
Body Mounting Hole Accommodation Length:
0.790 inches
Body Mounting Hole Accommodation Width:
0.438 inches
Distance Between Mounting Facility Centers:
1.078 inches
Mounting Hole Style:
Rectangular, w/two mounting holes/slots
Contact Maximum Current Rating In Amps:
3.0
Contact Material:
Phosphor bronze
Contact Surface Treatment:
Gold and silver
Accommodated Contact Quantity:
8
Polarization Type:
Colored dot
Projection Length Below Mounting Surface:
0.219 inches
Mounting Method:
Threaded stud
Mounting Type For Which Designed:
Chassis
Thready Qty Per Inch (tpi):
40
Thread Size:

0.112 inches

## NSN 5935-00-008-2464

Plug-in Electronic Components Socket - Page 2 of 2



**Contact Position Arrangement Style:** Dual in line **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.008 gold grains, troy and 0.008 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unc **Terminal Type And Quantity:** 8 solder well Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A02300