NSN 5935-00-008-5782

Steel

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-008-5782

Body Style:
Straight shape
Overall Length:
2.635 inches
Overall Height:
0.546 inches
Overall Width:
0.534 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
2.406 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
100 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Glass single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, cl 2 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Contact Material Specification:
Qq-b-616, comp 22 federal specification single material response single mating end single contact grouping
Shell Material:

NSN 5935-00-008-5782

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Chromate
Shell Material Specification:
Qq-s-698 federal specification single material response
Insert Material Specification:
Mil-m-19887 military specification single material response single mating end
Included Contact Quantity:
100 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Three spare contacts
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.100 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.