# NSN 5935-00-008-8268

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-008-8268

**Body Style:** 

Straight shape, external coupling

**Overall Height:** 

1.328 inches

**Overall Width:** 

1.328 inches

**Environmental Protection:** 

Moisture proof and salt water resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:** 

Between 0.115 inches and 0.130 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.062 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.062 inches

**Distance From Mounting Shoulder To Front Face:** 

Between 0.317 inches and 0.322 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

18-66 single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Polarization Method:** 

Keyway or multiple keyway

**Insert Position In Deg:** 

0.0

Shell Type:

Solid

**Connector Locking Method:** 

Bayonet pin

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Terminal Type:** 

Crimp single mating end single contact grouping

**Shell Material:** 

Aluminum alloy

**Shell Surface Treatment:** 

Cadmium and chromate

# NSN 5935-00-008-8268

Electrical Receptacle Connector - Page 2 of 2



Included	Contact	Quantity:
----------	---------	-----------

66 single mating end single contact grouping

# **Included Contact Type:**

Round socket single mating end single contact grouping

# **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

# **Precious Material And Weight:**

0.066 gold grains, troy and 0.066 silver grains, troy

#### **Precious Material:**

Gold and silver

#### **Test Data Document:**

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

81349-mil-c-38999 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

\_

Demilitarization:

No

Fiig:

A039b0

# Mil-std (military Standard):

Mil-c-38999 spec.