Electrical Receptacle Connector - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-00-009-2956

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
0.625 inches
Bushing Diameter:
0.250 inches
Overall Height:
Between 0.470 inches and 0.530 inches
Overall Width:
Between 0.470 inches and 0.530 inches
Unthreaded Mounting Hole Diameter:
Between 0.096 inches and 0.106 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 0.335 inches and 0.345 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 0.335 inches and 0.345 inches
Distance From Mounting Shoulder To Front Face:
0.310 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
Nonstd single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
36
Thread Size:
0.250 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping



Contact Surface Treatment: Gold single mating end single contact grouping **Insert Material:** Plastic tetrafluoroethylene single mating end **Contact Surface Treatment Specification:** Mil-g-45204, type 2, class @2 military specification single treatment response single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Contact Material Specification:** Qq-c-533, comp @ht federal specification single material response single mating end single contact grouping Shell Material: Steel **Included Contact Quantity:** 1 single mating end single contact grouping **Included Contact Type:** Coaxial socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.005 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Uns Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.