Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-009-3007

view Online	at https://aerobasegroup.com/nsn/5935-00-009-3007
Thread Cla	ss:
2a and 2b	
Thread Dire	ection:
Right-hand	and right-hand
Body Style	:
Hood, side	opening w/clamp
Overall Ler	ngth:
1.438 inche	S
Overall Hei	ght:
2.250 inche	S
Overall Wid	Jth:
0.438 inche	S
Cable Entra	ance Diameter:
0.313 inche	S
Threaded [Device Type:
Coupling fa	cility
Mating End	I Quantity:
1	
Contact Po	sition Arrangement Style:
9 single ma	ting end
Contact Re	movability:
Nonremova	ble single mating end single contact grouping
Contact Ma	aximum Current Rating In Amps:
7.5 single m	nating end single contact grouping
Polarizatio	n Method:
Jackscrew	
Shell Type:	:
Hood, side	opening
Connector	Locking Method:
Jackscrew-	socket
Connector	Cable Strain Relief Method:
Cable clam	þ
Thready Qt	y Per Inch (tpi):
40 and 40	
Thread Size	e:
0.112 inche	s and 0.112 inches
Terminal L	ocation:
Back single	mating end single contact grouping
Contact Ma	aterial:
Copper allo	y single mating end single contact grouping
Contact Su	Irface Treatment:
<u> </u>	

Gold single mating end single contact grouping

NSN 5935-00-009-3007

Electrical Plug Connector - Page 2 of 2



Insert Material: Plastic melamine single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Aluminum alloy Shell Surface Treatment: Anodize **Included Contact Quantity:** 9 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping **Precious Material And Location:** Contact surface gold **Precious Material And Weight:** 0.009 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc and unc Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0