

View Online at <https://aerobasegroup.com/nsn/5935-00-009-4524>

Body Style:

Angle, shape, internal coupling

Overall Length:

0.876 inches

Overall Height:

0.751 inches

Overall Diameter:

Between 0.359 inches and 0.391 inches

Environmental Protection:

Moisture resistant and salt water resistant and vibration resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

Bnc single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet latch

Connector Cable Strain Relief Method:

Compression nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic tetrafluoroethylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, class 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver

Shell Surface Treatment Specification:

Qq-s-365, type 2, gr a federal specification single treatment response

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact and shell surface silver

Precious Material And Weight:

0.005 gold grains, troy and 0.005 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.