## NSN 5935-00-009-6596

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-009-6596

**Body Style:** 

Embase female, w/guides

**Overall Length:** 

Between 4.291 inches and 4.301 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 3.871 inches and 3.879 inches

**Overall Height:** 

1.250 inches

**Overall Width:** 

Between 1.178 inches and 1.198 inches

**Environmental Protection:** 

Moisture resistant and salt water resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:** 

Between 0.280 inches and 0.285 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.562 inches

**Mating End Quantity:** 

**Contact Position Arrangement Style:** 

77 single mating end

**Contact Removability:** 

Removable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:** 

7.5 single mating end 2nd contact grouping

**Polarization Method:** 

Mating end

Shell Type:

Solid

**Terminal Location:** 

Back single mating end all contact groupings

**Contact Material:** 

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:** 

Gold single mating end all contact groupings

**Terminal Type:** 

Crimp single mating end all contact groupings

**Shell Material:** 

Aluminum alloy 6061

**Shell Surface Treatment:** 

Anodize

**Shell Surface Treatment Specification:** 

Mil-a-8625 military specification single treatment response

## NSN 5935-00-009-6596

Electrical Receptacle Connector - Page 2 of 2



Shell	Material	Specification:	

Qq-a-367, comp 6061, t6 federal specification single material response

**Included Contact Quantity:** 

65 single mating end 2nd contact grouping

**Included Contact Type:** 

Round socket single mating end all contact groupings

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.125 gold grains, troy

**Precious Material:** 

Gold

## **Test Data Document:**

81349-mil-c-265/18 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-c-26518 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-a-8625 spec.