NSN 5935-00-009-6645

Body Style:

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-009-6645

Straight shape, external coupling
Overall Length:
1.233 inches
Overall Height:
1.219 inches
Overall Width:
1.219 inches
Environmental Protection:
Moisture resistant and salt water resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.128 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.970 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.970 inches
Distance From Mounting Shoulder To Front Face:
0.632 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
15-15 single mating end
Contact Removability:
Removable single mating end all contact groupings
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end all contact groupings
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end all contact groupings
Terminal Type:
Crimp single mating end all contact groupings

NSN 5935-00-009-6645

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate and nickel
Shell Surface Treatment Specification:
Qq-p-416, type 2 federal specification 1st treatment response and qq-p-416, tt 2 federal specification 2nd treatment response and qq-n-290
federal specification 3rd treatment response
Included Contact Quantity:
14 single mating end 2nd contact grouping
Included Contact Type:
Round pin single mating end all contact groupings
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.024 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
96906-ms27466 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia: