

View Online at https://aerobasegroup.com/nsn/5935-00-009-8016

Th	read Class:
2a	and 2b
Th	read Direction:
Rig	ht-hand and right-hand
Во	dy Style:
Str	aight shape w/screw locks
Ov	erall Length:
Be	tween 3.640 inches and 3.660 inches
Οv	erall Height:
Be	tween 1.185 inches and 1.245 inches
Οv	erall Width:
Be	tween 0.240 inches and 0.260 inches
En	vironmental Protection:
Мс	isture resistant and salt water resistant and vibration resistant
Th	readed Device Type:
Co	upling facility
Ма	ting End Quantity:
1	
Co	ntact Position Arrangement Style:
2 r	ows of contacts non-inserted board single mating end
Po	larization Method:
Ja	ckscrew
Co	nnector Locking Method:
Jao	ckscrew-socket
Th	read Length:
0.1	25 inches and 0.125 inches
Th	ready Qty Per Inch (tpi):
56	
Th	read Size:
0.0	86 inches and 0.086 inches
Ins	ert Material:
Pla	stic diallyl phthalate glass filled or plastic polyphenylene single mating end
Ins	ert Material Specification:
Mil	-m-14, ty sdg-f military specification 1st material response or mil-p-46174 military specification 2nd material response single mating end
Th	read Series Designator:
Un	c and unc
Sh	elf Life:
N/a	à
Un	it Of Measure:
De	militarization:
No	



**Fiig:** A039b0

Mil-std (military Standard):

Mil-m-14 spec.