

View Online at <https://aerobasegroup.com/nsn/5935-00-010-6407>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, internal coupling

**Overall Length:**

7.680 inches

**Overall Diameter:**

2.250 inches

**Environmental Protection:**

Pressure proof

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

16-26 all mating ends

**Contact Removability:**

Nonremovable all mating ends single contact grouping

**Contact Maximum Current Rating In Amps:**

22.0 all mating ends single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 all mating ends single contact grouping

**Polarization Method:**

Key, multiple key groove

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Internally threaded coupling nut

**Thready Qty Per Inch (tpi):**

18

**Thread Size:**

1.750 inches

**Contact Surface Treatment:**

Gold all mating ends single contact grouping and nickel all mating ends single contact grouping

**Contact Surface Treatment Specification:**

Mil-g-45204, type 1, grade b military specification 1st treatment response all mating ends single contact grouping and qq-n-290, cl 1, grade b federal specification 2nd treatment response all mating ends single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Included Contact Quantity:**

26 all mating ends single contact grouping

**Included Contact Type:**

Round pin all mating ends single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.052 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.