NSN 5935-00-011-4730

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-011-4730 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling w/strain relief **Overall Length:** 1.906 inches **Body Length:** 2.516 inches **Overall Diameter:** 1.422 inches **Environmental Protection:** Heat resistant and vibration resistant **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 16-10 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 23.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 1st mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 1st mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Internally threaded coupling ring **Thread Size:** 1.000 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Nickel alloy single mating end 3rd contact grouping

NSN 5935-00-011-4730

Electrical Plug Connector - Page 2 of 2



| Contact Surface Treatment: |
|---|
| Gold single mating end single contact grouping |
| Insert Material: |
| Ceramic single mating end |
| Terminal Type: |
| Crimp single mating end single contact grouping |
| Shell Material: |
| Stainless steel |
| Included Contact Quantity: |
| 1 single mating end 3rd contact grouping |
| Included Contact Type: |
| Round pin single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.015 gold grains, troy |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Unef |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |