# NSN 5935-00-013-1080

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-013-1080

**Thread Class:** 2b and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Hood, top opening w/clamp **Overall Length:** 2.710 inches **Overall Height:** Between 2.035 inches and 2.105 inches **Overall Width:** 0.880 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 50 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Polarization Method:** Jackscrew Shell Type: Hood, side opening **Connector Locking Method:** Jackscrew-socket **Connector Cable Strain Relief Method:** Cable clamp **Thread Size:** 0.138 inches and 0.138 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** 

Insert Material:

Plastic melamine single mating end

Gold single mating end single contact grouping

# NSN 5935-00-013-1080

Electrical Plug Connector - Page 2 of 2



## **Contact Surface Treatment Specification:**

Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping

#### **Terminal Type:**

Solder well single mating end single contact grouping

# **Contact Material Specification:**

Qq-b-330, comp a federal specification single material response single mating end single contact grouping

#### **Shell Material:**

Aluminum alloy

#### **Shell Surface Treatment:**

Anodize

#### **Shell Surface Treatment Specification:**

Mil-a-8625, type 1 military specification single treatment response

#### **Insert Material Specification:**

Mil-m-14 ty mme military specification single material response single mating end

#### **Included Contact Quantity:**

50 single mating end single contact grouping

#### **Included Contact Type:**

Round socket single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

# **Precious Material And Weight:**

0.050 gold grains, troy

# **Precious Material:**

Gold

# **Test Data Document:**

81349-mil-c-8384 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Thread Series Designator:**

Unc and unc

#### **Specification Data:**

81349-mil-c-8384 government specification

## Shelf Life:

N/a

## **Unit Of Measure:**

## **Demilitarization:**

Nο

# Fiig:

A039b0

# Mil-std (military Standard):

Mil-g-45204 spec.