

View Online at <https://aerobasegroup.com/nsn/5935-00-013-9340>

**Body Style:**

Straight shape

**Overall Height:**

Between 3.094 inches and 3.124 inches

**Overall Width:**

Between 1.985 inches and 2.015 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

2.783 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.437 inches

**Distance From Mounting Shoulder To Front Face:**

0.344 inches

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

57 all mating ends

**Contact Removability:**

Removable all mating ends single contact grouping

**Contact Maximum Current Rating In Amps:**

7.5 all mating ends single contact grouping

**Polarization Method:**

1 polarization post

**Shell Type:**

Solid

**Terminal Location:**

Back all mating ends single contact grouping

**Contact Material:**

Copper alloy all mating ends single contact grouping

**Contact Surface Treatment:**

Gold all mating ends single contact grouping and silver all mating ends single contact grouping

**Insert Material:**

Plastic diallyl phthalate all mating ends

**Terminal Type:**

Crimp all mating ends single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Insert Material Specification:**

Mil-m-19833, type gdi-30f military specification single material response all mating ends

**Included Contact Type:**

Round socket all mating ends single contact grouping

**Special Features:**

Polarized at position 09

**Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:**

0.144 gold grains, troy and 0.144 silver grains, troy

**Precious Material:**

Gold and silver

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-m-19833 spec.