Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-013-9340

Body Style: Straight shape **Overall Height:** Between 3.094 inches and 3.124 inches **Overall Width:** Between 1.985 inches and 2.015 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 2.783 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.437 inches **Distance From Mounting Shoulder To Front Face:** 0.344 inches Mating End Quantity: **Contact Position Arrangement Style:** 57 all mating ends **Contact Removability:** Removable all mating ends single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 all mating ends single contact grouping **Polarization Method:** 1 polarization post Shell Type: Solid **Terminal Location:** Back all mating ends single contact grouping **Contact Material:** Copper alloy all mating ends single contact grouping **Contact Surface Treatment:** Gold all mating ends single contact grouping and silver all mating ends single contact grouping **Insert Material:** Plastic diallyl phthalate all mating ends **Terminal Type:** Crimp all mating ends single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium **Shell Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Insert Material Specification:**

2

Mil-m-19833, type gdi-30f military specification single material response all mating ends



Included Contact Type:

Round socket all mating ends single contact grouping

Special Features:

Polarized at position 09

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.144 gold grains, troy and 0.144 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.