

View Online at <https://aerobasegroup.com/nsn/5935-00-013-9931>

Thread Class:

2b and 2a

Thread Direction:

Right-hand and left-hand

Body Style:

Straight shape, internal coupling

Overall Length:

1.857 inches

Overall Diameter:

2.344 inches

Environmental Protection:

Fungus resistant and moisture resistant and corrosion resistant and vibration resistant and shock resistant

Threaded Device Type:

Coupling facility and back shell

Mating End Quantity:

1

Contact Removability:

Removable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

46.0 single mating end 1st contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling ring

Thready Qty Per Inch (tpi):

10 and 16

Thread Size:

2.000 inches and 1.875 inches

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end 2nd contact grouping and copper single mating end 2nd contact grouping

Terminal Type:

Crimp single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Oxide

Included Contact Quantity:

3 single mating end 1st contact grouping

Included Contact Type:

Round socket single mating end 2nd contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.036 gold grains, troy and 0.015 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Double stub and un

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0