Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-018-3492

Za
28
Thread Direction.
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.531 inches
Overall Height:
2.500 inches
Overall Width:
2.500 inches
Environmental Protection:
Watertight
Unthreaded Mounting Hole Diameter:
Between 0.171 inches and 0.177 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 1.933 inches and 1.943 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 1.933 inches and 1.943 inches
Distance From Mounting Shoulder To Front Face:
Between 0.875 inches and 0.885 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
36-10 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
13.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thread Length:

Electrical Receptacle Connector - Page 2 of 2



Thready Qty Per Inch (tpi):

16

Thread Size:

2.500 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Rubber single mating end

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Included Contact Quantity:

48 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.048 gold grains, troy and 0.048 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Un

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0