## NSN 5935-00-018-7343

**Plastic** 

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-018-7343

**Body Style:** Straight edge type w/card guide **Overall Length:** 3.320 inches **Overall Height:** 0.734 inches **Overall Width:** 0.453 inches **Unthreaded Mounting Hole Diameter:** 0.128 inches **Distance Between Mounting Facility Centers:** 3.070 inches **Board Accommodated Length:** 2.610 inches single board **Mating End Quantity: Contact Position Arrangement Style:** Bridged contacts inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 10.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 675.0 single mating end single contact grouping **Polarization Method:** Contact to contact polarizing keys Shell Type: Solid **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Tab, solder lug single mating end single contact grouping **Contact Material Specification:** Qq-3-330, comp a federal specification single material response single mating end single contact grouping **Shell Material:** 

## NSN 5935-00-018-7343

Electrical Receptacle Connector - Page 2 of 2



## **Insert Material Specification:**

Mil-m-14, type sdg-f military specification single material response single mating end

**Included Contact Quantity:** 

12 single mating end single contact grouping

**Included Contact Type:** 

Hermaphrodite single mating end single contact grouping

**Precious Material And Location:** 

Contact surface gold

**Precious Material And Weight:** 

0.012 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.