NSN 5935-00-018-9382

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-018-9382

Body Style:
Straight shape w/cable clamp
Overall Length:
1.125 inches
Bushing Diameter:
0.563 inches
Overall Height:
0.688 inches
Overall Width:
0.688 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.500 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.500 inches
Cable Entrance Diameter:
0.375 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
10s-2 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
50.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Bayonet latch
Connector Cable Strain Relief Method:
Compression nut
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping
Insert Material:

Terminal Type:

Crimp single mating end single contact grouping

Plastic tetrafluoroethylene single mating end

NSN 5935-00-018-9382

Fiig: A039b0

Electrical Receptacle Connector - Page 2 of 2



Contact Material Specification:
Qq-c-530, comp a federal specification single material response single mating end single contact grouping
Shell Material:
Copper alloy
Shell Surface Treatment:
Silver
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial pin single mating end single contact grouping
Precious Material And Location:
Contact and shell surfaces silver
Precious Material And Weight:
0.105 silver grains, troy
Precious Material:
Silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No