

View Online at <https://aerobasegroup.com/nsn/5935-00-018-9387>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape w/cable clamp

Overall Length:

1.130 inches

Bushing Diameter:

0.500 inches

Overall Height:

0.690 inches

Overall Width:

0.690 inches

Environmental Protection:

Corrosion resistant and moisture resistant and shock resistant and vibration resistant

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.500 inches

Cable Entrance Diameter:

0.333 inches

Distance From Mounting Shoulder To Front Face:

0.550 inches

Threaded Device Type:

Mounting hole

Mating End Quantity:

1

Contact Position Arrangement Style:

Bnc single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1000.0 single mating end single contact grouping

Contact Maximum Frequency Rating:

5.0 megahertz single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Connector Cable Strain Relief Method:

Cable clamp

Thready Qty Per Inch (tpi):

56

Thread Size:

0.099 inches

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204, type 2, class 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Copper alloy

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.