Electrical Connector Shell - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-020-8010

| nread Class: |
|--|
| a |
| nread Direction: |
| ight-hand |
| verall Length: |
| etween 1.359 inches and 1.391 inches |
| enter To Center Distance Between Mounting Facilities Parallel To Width |
| etween 1.745 inches and 1.755 inches |
| verall Height: |
| etween 2.219 inches and 2.281 inches |
| verall Width: |
| etween 2.219 inches and 2.281 inches |
| nthreaded Mounting Hole Diameter: |
| etween 0.118 inches and 0.128 inches |
| enter To Center Distance Between Mounting Facilities Parallel To Heigh |
| etween 1.745 inches and 1.755 inches |
| nread Length: |
| 438 inches |
| ze Designation: |
| 2 |
| ounting Facility Type And Quantity: |
| threaded coupling and 4 unthreaded hole |
| nready Qty Per Inch (tpi): |
| 3 |
| nread Size: |
| 750 inches |
| aterial: |
| uminum |
| aterial: |
| uminum |
| urface Treatment: |
| admium |
| tyle Designator: |
| px/wall mount external thread |
| urface Treatment: |
| admium |
| nread Series Designator: |
| ns |
| helf Life: |
| /a |
| nit Of Measure: |
| |
| |

NSN 5935-00-020-8010

Electrical Connector Shell - Page 2 of 2

Demilitarization:

No

Fiig:

A10100

