NSN 5935-00-020-8038

Thread Class:

Right-hand **Body Style:**

Thread Direction:

Overall Length:

Angle, shape, internal coupling

2b

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-020-8038

| 0.656 inches |
|--|
| Overall Height: |
| 0.719 inches |
| Overall Diameter: |
| 0.312 inches |
| Cable Entrance Diameter: |
| Between 0.116 inches and 0.119 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| Nonstd single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Internally threaded coupling ring |
| Connector Cable Strain Relief Method: |
| Compression nut |
| Thread Size: |
| 0.250 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Insert Material: |
| Plastic tetrafluoroethylene single mating end |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Shell Material: |
| |
| Copper alloy |
| Copper alloy |

NSN 5935-00-020-8038Electrical Plug Connector - Page 2 of 2



| Shell Surface Treatment: | |
|---|--|
| Gold | |
| ncluded Contact Quantity: | |
| 1 single mating end single contact grouping | |
| ncluded Contact Type: | |
| Coaxial pin single mating end single contact grouping | |
| Precious Material And Location: | |
| Contact and shel surfaces gold | |
| Precious Material And Weight: | |
| 0.105 gold grains, troy | |
| Precious Material: | |
| Gold | |
| Thread Series Designator: | |
| Jnef | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| - | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A039b0 | |