## NSN 5935-00-022-5792

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-022-5792 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Angle shape, external coupling **Overall Length:** 1.780 inches **Overall Height:** 1.000 inches **Overall Diameter:** 1.724 inches **Environmental Protection:** Thermal shock resistant and vibration resistant **Distance From Mounting Shoulder To Front Face:** 0.825 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Spring friction **Connector Cable Strain Relief Method:** Cable clamp Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping **Thread Size:** 0.500 inches **Terminal Location:** Back single mating end single contact grouping **Insert Material:** 

Plastic tetrafluoroethylene single mating end

**Terminal Type:** 

Solder well single mating end single contact grouping

## NSN 5935-00-022-5792

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Copper alloy
Included Contact Quantity:
1 single mating end single contact grouping
<b>Bushing Accommodation Hole Shape:</b>
Round
Included Contact Type:
Coaxial socket single mating end single contact grouping
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0