Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-022-9994

# Thread Class: 2a and 2a Thread Direction: Right-hand and right-hand Body Style: Straight shape, external coupling Overall Length: 1.562 inches

**Overall Diameter:** 

1.000 inches

**Environmental Protection:** 

Moisture proof and salt water resistant and vibration resistant

# Distance From Mounting Shoulder To Front Face:

0.891 inches

### Mounting Facility Thickness:

0.109 inches

### Threaded Device Type:

Coupling facility and mounting bushing

# Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

Tnc single mating end

#### **Contact Removability:**

Nonremovable single mating end single contact grouping

### Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

#### Shell Type:

Solid

#### **Connector Locking Method:**

Externally threaded shell

#### **Connector Cable Strain Relief Method:**

Compression nut

### Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

#### Thread Size:

0.438 inches and 0.750 inches

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

### **Contact Surface Treatment:**

Gold single mating end single contact grouping

Electrical Receptacle Connector - Page 2 of 2



**Insert Material:** Plastic tetrafluoroethylene single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Copper alloy Shell Surface Treatment: Silver **Included Contact Quantity:** 1 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round w/flat **Included Contact Type:** Coaxial socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and shell surface silver **Precious Material And Weight:** 0.005 gold grains, troy and 0.100 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unef and un Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0