NSN 5935-00-023-2377

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-023-2377 **Thread Class:** 2a and 2b and 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 1.500 inches **Overall Height:** 0.380 inches **Overall Width:** 0.530 inches **Distance Between Mounting Facility Centers:** 1.281 inches **Threaded Device Type:** Coupling facility and mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 44 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Polarization Method:** Jackscrew **Connector Locking Method:** Jackscrew-socket **Thread Length:** 0.150 inches Thready Qty Per Inch (tpi): **Thread Size:** 0.086 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold and nickel single mating end single contact grouping

Insert Material:

Plastic single mating end

NSN 5935-00-023-2377

A039b0

Electrical Receptacle Connector - Page 2 of 2



| Terminal Type: |
|--|
| Solder well single mating end single contact grouping |
| Unable To Decode: |
| Unable to decode and unable to decode |
| Included Contact Quantity: |
| 44 single mating end single contact grouping |
| Included Contact Type: |
| Round pin single mating end single contact grouping |
| Special Features: |
| Jackscrew type-female and location-left handandjackscrew type-male and location-right hand |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.044 gold grains, troy |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |