

View Online at <https://aerobasegroup.com/nsn/5935-00-023-6633>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight edge type

**Overall Length:**

3.203 inches

**Overall Height:**

0.313 inches

**Overall Width:**

0.406 inches

**Unthreaded Mounting Hole Diameter:**

0.141 inches

**Distance Between Mounting Facility Centers:**

2.813 inches

**Board Accommodated Length:**

2.450 inches single board

**Threaded Device Type:**

Mounting stud

**Board Accommodated Width:**

0.125 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

11 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

1100.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

1500.0 single mating end single contact grouping

**Polarization Method:**

Guide pin/socket

**Connector Locking Method:**

Screw lock pin

**Thread Length:**

0.375 inches

**Thread Size:**

0.112 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Terminal Type:**

Pin single mating end single contact grouping

**Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

**Insert Material Specification:**

Mil-m-19833, type gdi-30f military specification single material response single mating end

**Included Contact Quantity:**

11 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-m-19833 spec.