## NSN 5935-00-024-0456

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-024-0456

**Body Style:** 

Straight shape, internal coupling w/strain relief

**Body Length:** 

2.375 inches

**Overall Diameter:** 

Between 1.798 inches and 1.828 inches

**Environmental Protection:** 

Moisture resistant and salt water resistant and vibration resistant

**Cable Entrance Diameter:** 

0.938 inches

**Mating End Quantity:** 

4

**Contact Position Arrangement Style:** 

61-5 single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

7.5 single mating end 2nd contact grouping

**Polarization Method:** 

Keyway or multiple keyway

**Insert Position In Deg:** 

0.0

Shell Type:

Solid

**Connector Locking Method:** 

Spring friction

**Connector Cable Strain Relief Method:** 

Cable clamp

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end 1st contact grouping

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Insert Material:** 

Plastic silicone single mating end

**Terminal Type:** 

Crimp single mating end single contact grouping

**Shell Material:** 

Aluminum alloy

## NSN 5935-00-024-0456

Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium
Included Contact Quantity:
49 single mating end 2nd contact grouping
Included Contact Type:
Round pin single mating end 2nd contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0