

View Online at <https://aerobasegroup.com/nsn/5935-00-024-0584>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, external/internal coupling

**Overall Length:**

1.576 inches

**Environmental Protection:**

Moisture resistant and salt water resistant and vibration resistant

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

Nonstd 1st mating end

**Contact Removability:**

Nonremovable all mating ends all contact groupings

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet latch and externally threaded shell

**Thready Qty Per Inch (tpi):**

36

**Thread Size:**

0.250 inches

**Contact Material:**

Copper alloy all mating ends all contact groupings

**Contact Surface Treatment:**

Gold all mating ends all contact groupings

**Insert Material:**

Plastic tetrafluoroethylene all mating ends

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, class 2 military specification single treatment response all mating ends all contact groupings

**Contact Material Specification:**

Qq-c-530, comp ht federal specification single material response all mating ends all contact groupings

**Shell Material:**

Steel comp 303

**Shell Surface Treatment:**

Passivate

**Shell Material Specification:**

Qq-s-763, class 303 federal specification single material response

**Included Contact Quantity:**

1 2nd mating end single contact grouping

**Included Contact Type:**

Coaxial socket 2nd mating end single contact grouping

**Precious Material And Location:**

Contact surface gold

**Precious Material And Weight:**

0.010 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.