

View Online at <https://aerobasegroup.com/nsn/5935-00-025-6386>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape w/flange

Mounting Hole Circle Radius:

2.812 inches

Overall Diameter:

5.688 inches

Unthreaded Mounting Hole Diameter:

0.219 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

10.0 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

125.0 single mating end all contact groupings

Polarization Method:

Contact

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

7

Thread Size:

1.938 inches

Terminal Location:

Front single mating end 2nd contact grouping

Contact Material:

Copper alloy single mating end all contact groupings

Insert Material:

Plastic single mating end

Terminal Type:

Screw single mating end all contact groupings

Shell Material:

Plastic

Shell Material Specification:

Mil-m-14, type mai-60 military specification single material response

Insert Material Specification:

Mil-m-14, type mai-60 military specification single material response single mating end

Included Contact Quantity:

3 single mating end 2nd contact grouping

Test Data Document:

81349-mil-r-2726 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Specification Data:

81349-mil-r-2726/67 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.