NSN 5935-00-025-6386

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-025-6386 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape w/flange **Mounting Hole Circle Radius:** 2.812 inches **Overall Diameter:** 5.688 inches **Unthreaded Mounting Hole Diameter:** 0.219 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Removability:** Nonremovable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 10.0 single mating end all contact groupings **Contact Maximum Ac Voltage Rating In Volts:** 125.0 single mating end all contact groupings **Polarization Method:** Contact Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 7 **Thread Size:** 1.938 inches **Terminal Location:** Front single mating end 2nd contact grouping **Contact Material:** Copper alloy single mating end all contact groupings **Insert Material:** Plastic single mating end **Terminal Type:** Screw single mating end all contact groupings

Shell Material: Plastic

NSN 5935-00-025-6386

Electrical Receptacle Connector - Page 2 of 2



Shell Material Specification:

Mil-m-14, type mai-60 military specification single material response

Insert Material Specification:

Mil-m-14, type mai-60 military specification single material response single mating end

Included Contact Quantity:

3 single mating end 2nd contact grouping

Test Data Document:

81349-mil-r-2726 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Specification Data:

81349-mil-r-2726/67 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.