## NSN 5935-00-027-0245

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-027-0245 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling w/strain relief **Body Length:** Between 1.675 inches and 1.737 inches **Overall Diameter:** 1.030 inches **Environmental Protection:** Pressure proof and moisture resistant and vibration resistant **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 10sl-3 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 200.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 1250.0 single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 0.0 Shell Type: **Connector Locking Method:** Internally threaded coupling ring Thread Length: 0.312 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.625 inches

Terminal Location:

Back single mating end single contact grouping

## NSN 5935-00-027-0245

Electrical Plug Connector - Page 2 of 2



Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Rubber synthetic single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Insert Material Specification:
Mil-r-3065 military specification single material response single mating end
Included Contact Quantity:
3 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.003 gold grains, troy and 0.003 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig:

A039b0

Mil-std (military Standard):

Mil-r-3065 spec.