NSN 5935-00-027-6714

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-027-6714 **Thread Class:** 2b **Thread Direction:** Right-hand **Overall Length:** 3.410 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 3.000 inches **Overall Height:** 1.250 inches **Overall Width:** 1.130 inches **Environmental Protection:** Vibration resistant Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.750 inches **Threaded Device Type:** Mounting hole **Mating End Quantity: Contact Position Arrangement Style:** 34 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 10.0 single mating end single contact grouping **Polarization Method:** Guide pin/socket Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.138 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping **Included Contact Quantity:**

34 single mating end single contact grouping

NSN 5935-00-027-6714

Electrical Receptacle Connector - Page 2 of 2



Included	Contact	Ty	pe:
----------	---------	----	-----

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.034 gold grains, troy and 0.034 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0