## NSN 5935-00-032-9732

Thread Class: 2a and 2a

**Body Style:** 

Overall Length: 1.375 inches

**Thread Direction:** 

Right-hand and right-hand

Straight shape, external coupling

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-032-9732

Overall Diameter:
0.812 inches
Cable Entrance Diameter:
0.142 inches
Mounting Facility Thickness:
0.250 inches
Threaded Device Type:
Coupling facility and mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
N single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Connector Cable Strain Relief Method:
Compression nut
Thread Size:
0.625 inches and 0.625 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic tetrafluoroethylene single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Steel

## NSN 5935-00-032-9732

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:	
Passivate	
Included Contact Quantity:	
1 single mating end single contact grouping	
Bushing Accommodation Hole Shape:	
Round w/double flat	
Included Contact Type:	
Coaxial socket single mating end single contact grouping	
Precious Material And Location:	
Contact surface gold	
Precious Material And Weight:	
0.005 gold grains, troy	
Precious Material:	
Gold	
Thread Series Designator:	
Unef and unef	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	